



SODLC 36 / SODLC 50

Suction Overlap Feed, Double Side Lamination with Auto cutter

Technical Specifications

MODEL	SODLC 36	SODLC 50
Lamination	Double Side	Double Side
Max. Laminating Width	360 mm	500 mm
Unwinder Diameter	300 mm (max), Core Dia 1" & 3"	
Operating Speed	14 meters / minute	
Paper Thickness	125~350 gsm	
Laminating Temperature	90~110 °C (Normal)	
Total Power	2200 W	
Temperature Control	Upper / lower Controlled Separately	
Upper Heating Roller	Steel roll (Standard)	
Lower Heating Roller	Rubber roller	
Control Panel	7" Touch Panel	
Feeding System	Suction Feeding	
Overlap Feeding Function	Yes	
Heater Warm-Up Time	5 minutes	
Paper Stacking Capacity	15 cm	
Auto Bursting Function	Yes (Auto Sheet Separation)	
Slitting Function	Yes	
Anti-Curling Function	Yes	
Compressor	Standard Supply	
Conveyor Belt	Not Applicable	
Power Supply	220 V, 50 Hz (Single Phase)	
Dimensions (L × W × H)	185x75x147 cm	199x89x147 cm

Optionals

1. Upper Re-winder -For Foil Applications (For both the models)
2. Lower Re-winder- To wind the laminated materials